

# EDGE-mini

ILF2-1,5R-8x180DL12(111)

## Application

Ultrasmall luminaire for monochrome lighting of window openings. One tiny lighting device that will provide even lighting of the entire width of the window opening with a beam of 8x180 degrees. The luminaire can be also used for lighting of niches and prominent elements of any facade or interior.

<b>Light source</b>	Cree (USA)
<b>Light color</b>	Red
<b>CRI</b>	≥ 80
<b>Luminous flux</b>	35 lm
<b>Optics</b>	8x180°
<b>Operating voltage</b>	DC 12 V
<b>Power input</b>	4,5 W
<b>Control</b>	PWM
<b>Electrical class</b>	III (third)
<b>Operating temperature:</b>	
-for standard edition	-40 °C...+45 °C
-for tropic edition	-40 °C...+55 °C
<b>Lifespan</b>	Not less than 50 000 hours
<b>Warranty</b>	3-5 years
<b>Weight</b>	0,3 kg
<b>Dimensions</b>	ø61 x 52 mm
<b>Materials</b>	Luminaire housing: cast aluminum, powder coated; mounting plate: stainless steel.
<b>Mounting</b>	Attachable to a surface using a mounting plate, bracket-mounted.
<b>Accessories</b>	Aperture, mounting plate
<b>Customization</b>	Housing and mounting plate painting in any color in accordance with RAL palette; IP68 connectors; operating temperature of -40 °C ... +55 °C (tropical version).



IP65

IK08

