

GROUND-mini IRG1-1A-120H(241)

Application

Ground-mini — a marker luminaire designed to create accents in landscape lighting. Minimalistic design makes Ground-mini a universal tool of a lighting designer.

| | |
|-------------------------------|---|
| Light source | Cree (USA) |
| Light color | Amber |
| CRI | ≥ 80 |
| Luminous flux | 20 lm |
| Optics | 120° |
| Pulsation coefficient | 5% |
| Voltage | AC 230 V, (50±1) Hz |
| Power input | 3,5 W |
| Power factor Cos | 0,5 |
| Control | No |
| Electrical class | I (first) |
| Operating temperature: | |
| -for standard edition | -40 °C...+45 °C |
| -for tropic edition | -40 °C...+55 °C |
| Lifespan | Not less than 50 000 hours |
| Warranty | 5 years |
| Weight | 0,5 kg |
| Dimensions | Ø74,5x94 mm |
| Mounting | Build into the ground or concrete with different surfaces (asphalt, paving slab, facing stone etc.) |
| Customization | Control/power cables of any length |
| Materials | Housing: pressure-cast aluminum, covered with powder paint; protective glass: hardened with silicon sealer; mounting curb: ABS plastic; decorative frame: polished stainless steel; mounts: stainless steel |

