INTILED

GROUND-mini

IRG1-1,5W40-60DL12(131)

Application
A compact inground marker light fixture designed for both functional and decorative illumination purposes.

Light color	White 4000 K
CRI	> 80
Color binning	2 MacAdam steps
Optics, degrees	60
Delivered lumens, lm	60
Voltage, V	12 DC
Wattage, W	1,5
Power factor	
Electric class	III (third)
Protection class	IP67
Operating temperature, degrees C	-40 ... +55
IK rating	IK10
Control, protocols	PWM
Control, pixel size	
Lifespan, hours	Not less than 50 000
Warranty, years	5
Dimensions, mm	Ø88x97
Weight, kg	0,53
Content of delivery	Luminaire, package, passport, mounting instructions





Mounting
In-ground

Materials
Housing — aluminum casting alloy, covered with powder paint; protective glass — silicate tempered glass, 8 mm thick, with silicon sealer; mounting curb – polypropylene; decorative frame — polished stainless steel; metalware — stainless steel.

Integrated technologies
Aquatech® technology – a multi-stage protection technology safeguards luminaires against water ingress.

INTILED

Additional codes definition

(131) - Transparent hardened glass, round frame, 90 mm diameter;
(141) - Transparent hardened glass, square frame, 90 mm side length;
(231) - Matte hardened glass, round frame, 90 mm diameter;
(241) - Matte hardened glass, square frame, 90 mm side length.

Accessories

Customized accessories are manufactured according to the project

Compatible control system devices

LightCAD software key x2

LightCAD software key x8

LightCAD software key x32

LightCAD software key x64

LightCAD software key x128

LightCAD software key x512

Controller LED-IPCe

Controller LED-IPCs

Converter U-Box 8

Converter U-Box 4

Converter Din-Box 8

Converter Din-Box 6

Converter Din-Box 2

Splitter DMX (B1T2)

Splitter DMX (B4)

Converter UCS-ILCS

Converter DAP-04

Converter DMX-DIM(T1)