

KUB

IMF4-2FC-125CL24(111)

Application

KUB low power luminaire is designed primarily for accent lighting of facade elements.

The compact dimensions make it possible to place KUB on columns, visors, in narrow inter-window spaces, on decorative details. A unique adjustment system allows you to quickly mount and adjust the luminaire using a regular hexagon screwdriver.

Light source OSRAM (Germany)

Light color Full color

CRI -

Luminous flux:

- for «FC» 150 lm

- for «RGB» 134 lm

- for «R» 69 lm

- for «G» 283 lm

- for «B» 61 lm

- for «W» 457 lm

Optics 125°

Voltage DC 24 V

Power input:

- for «FC» 7 W

- for «W» 8 W

Control DMX

Electrical class III (third)

Operating temperature:

-for standard edition -40 °C...+45 °C

-for tropic edition -40 °C...+55 °C

Lifespan Not less than 50 000 hours

Warranty 5 years

Weight 1,4 kg

Dimensions 171x104x100 mm
(with bracket)

Materials housing, bracket: aluminum alloy; mounts: stainless steel; silicate tempered glass

Mounting on an adjustable bracket

Accessories shield

Customization

diffuser glass; internal honeycomb louvre; customized LEDs color combinations; control/power cables of any length up to 3 m; housing and accessories painting in any RAL color; IP68 connectors



IP66 IK08

