

# KUB

## IMF4-2FC-15CH(111)

### Application

KUB low power luminaire is designed primarily for accent lighting of facade elements.

The compact dimensions make it possible to place KUB on columns, visors, in narrow inter-window spaces, on decorative details. A unique adjustment system allows you to quickly mount and adjust the luminaire using a regular hexagon screwdriver.

**Light source** OSRAM (Germany)

**Light color** Full color

**CRI** -

### Luminous flux:

- for «FC» 150 lm

- for «RGB» 120 lm

- for «R» 62 lm

- for «G» 254 lm

- for «B» 42 lm

- for «W» 411 lm

**Optics** 15°

**Pulsation coefficient** 5%

**Voltage** AC 230 V, (50±1) Hz

### Power input:

- for «FC» 9 W

- for «W» 10,5 W

**Power factor Cos** 0,9

**Control** DMX

**Electrical class** I (first)

### Operating temperature:

-for standard edition -40 °C...+45 °C

-for tropic edition -40 °C...+55 °C

**Lifespan** Not less than 50 000 hours

**Warranty** 5 years

**Weight** 1,4 kg

**Dimensions** 171x104x100 mm  
(with bracket)

**Materials** housing, bracket: aluminum alloy; mounts: stainless steel; silicate tempered glass

**Mounting** on an adjustable bracket

**Accessories** shield

**Customization** diffuser glass; internal honeycomb louvre; customized LEDs color combinations; control/power cables of any length up to 3 m; housing and accessories painting in any RAL color; IP68 connectors



CE  IP66 IK08

