

LINE-antiglare

ILF21-1,5W40-50H-90(10BKL1)

Application

LINE antiglare — a stylish solution for comfortable lighting of the entrance group. The optical system with an additional anti-glare reflector reduces the level of visual discomfort and ensures a glare rating of UGR<19. The variety of custom brackets allows for easy recessed or suspended installation of the fixture into the rack ceilings.



Light color	White 4000 K
CRI	> 80
Color binning	2 MacAdam steps
Optics, degrees	50
Delivered lumens, lm	3 850
Voltage, V	230 AC 50 Hz
Wattage, W	36
Power factor	> 0,9
Electric class	I (first)
Protection class	IP66
Operating temperature, degrees C	-40 ... +55
IK rating	IK08
Control, protocols	On/Off
Control, pixel size	
Lifespan, hours	Not less than 50 000
Warranty, years	5
Dimensions, mm	900x56x71
Weight, kg	2,6
Content of delivery	Luminaire, package, passport, mounting instructions

Mounting

Built-in to the ceiling


Materials

Housing — extruded aluminum section, covered with powder paint; protective glass — silicate tempered glass; end caps — aluminum casting alloy, covered with powder paint; bracket — aluminum casting alloy, stainless steel/zink-plated steel, covered with powder paint; metalware — stainless steel.



Integrated technologies

EternalTechnology® is a continuous monitoring of the internal temperature of the lighting fixture through the system of integrated sensors.
Truelight® technology - a comprehensive suite of solutions designed to deliver flawless lighting effects.
Aquatech® technology – a multi-stage protection technology safeguards luminaires against water ingress.
COOLight® technology is aimed at increasing the efficiency of lighting fixtures.

Standard RAL colors



Standard coating type
moire



Additional codes definition

(10BKL1) - basic additional version

Accessories

Compatible control system devices