

# PILL

## IRF1-3R-15L24

### Application

Ultra-compact accent lighting fixture, intended for lighting of tiny facade details or precise landscape lighting.

|                               |   |
|-------------------------------|---|
| <b>Light color</b>            | Red   |
| <b>CRI</b>                    | -   |
| <b>Delivered lumen output</b> | 65 lm   |
| <b>Luminous Efficiency</b>    | 22 lm/W   |
| <b>Optics</b>                 | 15°   |
| <b>Voltage</b>                | 24 V DC   |
| <b>Power input</b>            | 3 W   |
| <b>Control</b>                | No  |
| <b>Electrical class</b>       | III (third)   |
| <b>Operating temperature</b>  | -40 °C...+55 °C   |
| <b>Lifespan</b>               | not less than 50 000 hours  |
| <b>Warranty</b>               | 5 years   |
| <b>Weight</b>                 | 0,3 kg  |
| <b>Dimensions</b>             | 48x48x66 mm   |
| <b>Materials</b>              | housing, bracket – die-cast aluminum; diffusor – polycarbonate  |
| <b>Mounting</b>               | on an adjustable bracket  |
| <b>Accessories</b>            | shield  |
| <b>Customization</b>          | housing and accessories painted in any RAL color; IP68 connectors; power cables of any length up to 3 m |

