

RAY

IMF20-1RGBA-10RH(111)

Application

RAY luminaire is designed for flood and accent architectural lighting.

Light source

Cree (USA)

Light color

Red + Green + Blue
+ Amber

CRI

≥ 80

Luminous flux:

- for «RGBA» 1100 lm

- for «RGB» 780 lm

- for «R» 250 lm

- for «G» 395 lm

- for «B» 135 lm

- for «A» 345 lm

Optics

10°

Pulsation coefficient

5%

Voltage

AC 230 V, (50±1) Hz

Power input

26 W

Power factor Cos

0,95

Control

RDM+DMX

Electrical class

I (first)

Operating temperature:

-for standard edition

-40 °C...+45 °C

-for tropic edition

-40 °C...+55 °C

Lifespan

Not less than 50 000 hours

Warranty

3-5 years

Weight

2 kg

Dimensions

290x140x94 mm (with bracket)

Materials

Device enclosure: aluminum alloy; protective glass: tempered glass; mounting arms: cast aluminum alloy covered with powder paint to fit the luminaire color; mounts: stainless steel

Mounting

On an adjustable bracket

Accessories

Blind, lattice

Customization

Diffuser glass, internal honeycomb lattice, control/power cables of any length up to 3 m, housing and accessories painting in any RAL color, production of customized accessories, IP68 connectors



IP65 IK08

