

SPOT

IMF1-2W40-15x60H

Application

The new SPOT accent luminaire with an updated design and enhanced features. It integrates the latest cutting-edge technical innovations from INTILED.



Light color	White 4000 K
CRI	> 80
Color binning	2 MacAdam steps
Optics, degrees	15x60
Delivered lumens, lm	330
Voltage, V	230 AC 50 Hz
Wattage, W	6
Power factor	> 0,9
Electric class	I (first)
Protection class	IP66
Operating temperature, degrees C	-40 ... +55
IK rating	IK09
Control, protocols	On/Off
Control, pixel size	
Lifespan, hours	Not less than 50 000
Warranty, years	5
Dimensions, mm	69x143x109
Weight, kg	0,75
Content of delivery	Luminaire, package, passport, mounting instructions

Mounting

Surface mounted, on a swivel bracket.

Materials

Housing, bracket – aluminum casting alloy, covered with powder paint; protective glass — silicate tempered glass; metalware — stainless steel.

Integrated technologies

EternalTechnology® is a continuous monitoring of the internal temperature of the lighting fixture through the system of integrated sensors.

Truelight® technology - a comprehensive suite of solutions designed to deliver flawless lighting effects.

Aquatech® technology – a multi-stage protection technology safeguards luminaires against water ingress.

Standard RAL colors

1015

1001

8004

8017

9005


7016

9006

9003

Standard coating type

moire



Additional codes definition

Accessories

brackets

SPOT-01-110 - for the pole, swivel (1 hole)

SPOT-02-110 - for the pole, swivel (2 holes)

SPOT-03-070 - for the pole, static

spikes

SPOT-01-400-55 - into the ground, 400 mm depth, 55 mm height

SPOT-02-400-150 - into the ground, 400 mm depth, 150 mm height

tubes

SPOT-01-050 - 50 mm height

screens

SPOT-03-050 - 50 mm height

Compatible control system devices