

TWIN-lite

IMF8-1B-30H

Application

TWIN-lite is a single-sided version of the TWIN luminaire. It is designed for façade applications in areas close to the observer, where maximum aesthetic appeal, visual consistency, and uniformity of shape and lighting effects are essential. TWIN-lite is an ideal complement to the TWIN and KUB luminaires.



Light color	Blue
CRI	
Color binning	±3 nm
Optics, degrees	30
Delivered lumens, lm	230
Voltage, V	230 AC 50 Hz
Wattage, W	10
Power factor	> 0,9
Electric class	I (first)
Protection class	IP66
Operating temperature, degrees C	-40 ... +55
IK rating	IK08
Control, protocols	On/Off
Control, pixel size	
Lifespan, hours	Not less than 50 000
Warranty, years	5
Dimensions, mm	103x155x180
Weight, kg	2
Content of delivery	Luminaire, package, passport, mounting instructions

Mounting

Surface mounted

Materials

Housing, bracket — extruded aluminum; diffuser — silicate tempered glass.


Integrated technologies

EternalTechnology® is a continuous monitoring of the internal temperature of the lighting fixture through the system of integrated sensors.

Standard RAL colors

1015	1001	8004	8017
9005	7016	9006	9003

Standard coating type
moire



Additional codes definition

Accessories

Customized accessories are manufactured according to the project

Compatible control system devices